

Product No.	Size	Description	Ctn. Qty.	Ctn. Wt.	U.P.C. Code	MSDS
<b>STA PUT®</b>						
<ul style="list-style-type: none"> <li>Superior grade of plumbers' putty</li> <li>Flexible, stretchable compound; molds easily</li> </ul>			<ul style="list-style-type: none"> <li>Will not harden, crumble, crack or shrink</li> </ul>			
25101	14 oz.		24	22.9	032628251014	22
25103	3 lb.		12	38.5	032628251038	22
25105	5 lb.		6	32.0	032628251052	22
25110	7 lb.	PLASTIC PAIL WITH HANDLE	6	45.0	032628251106	22
25120	20 lb.	PLASTIC PAIL WITH HANDLE	2	43.0	032628251205	22
<b>STA PUT ULTRA®</b>						
<ul style="list-style-type: none"> <li>Non-staining polymer sealant</li> <li>Permanently soft, malleable, and flexible</li> </ul>			<ul style="list-style-type: none"> <li>Unique, professional grade</li> </ul>			
25171	14 oz.		12	22.9	032628251717	108
<b>PLASTIC SEAL™</b>						
<ul style="list-style-type: none"> <li>Multi-purpose caulk &amp; repair product</li> <li>Waterproof</li> </ul>			<ul style="list-style-type: none"> <li>Ideal lead substitute in lead/oakum joints</li> </ul>			
25215	10.3 oz.	CARTRIDGE	12	18.0	03262825158	91
<b>ROOF &amp; FLASHING SEALANT</b>						
<ul style="list-style-type: none"> <li>Long-lasting sealant</li> <li>No separation; no stirring time; no objectionable odor</li> </ul>			<ul style="list-style-type: none"> <li>Forms durable, flexible, weatherproof coating</li> <li>Can be applied on cold or wet surfaces</li> </ul>			
25403	10.3 oz.	CARTRIDGE	12	10.1	032628254039	26
25405	1 qt.		12	30.0	032628254053	26
25410	1 gal.		6	57.5	032628254107	26
25415	5 gal.		1	45.0	032628254152	26
<b>PRO POXY® 20</b>						
<ul style="list-style-type: none"> <li>Cures in 20 minutes</li> <li>Mixes quickly and easily</li> </ul>			<ul style="list-style-type: none"> <li>Seals, mends, bonds and repairs almost anything</li> </ul>			
25515	4 oz.	DISPLAY PACK (2 - 1 DZ.)	24	8.0	032628255159	24
<b>PLASTIC POXY™</b>						
<ul style="list-style-type: none"> <li>For most plastics</li> <li>Fully hardens in 40 minutes</li> </ul>			<ul style="list-style-type: none"> <li>Mixes quickly and easily</li> </ul>			
25531	4 oz.	DISPLAY PACK (2 - 1 DZ.)	24	8.0	032628255319	86
<b>PLUMBERS CAULK™</b>						
<ul style="list-style-type: none"> <li>Siliconized acrylic-latex plumbers caulk</li> <li>Flows easily, does not harden in tube or cartridge; will not crumble, resists shrinkage</li> </ul>			<ul style="list-style-type: none"> <li>Flexible, durable, extremely mildew-resistant, waterproof</li> </ul>			
25605	6 fl oz.	WHITE - TUBE DISPLAY	24	16.5	032628256057	28
25615	11 fl oz.	WHITE - CARTRIDGE	12	15.0	032628256156	28
25620	5.5 fl oz.	CLEAR - TUBE DISPLAY	24	16.5	032628256200	71
25625	10.3 fl oz.	CLEAR - CARTRIDGE	12	15.0	032628256255	71
25631	5.5 fl oz.	ALMOND/BONE - TUBE DISPLAY	24	16.5	032628256316	73
25636	10.3 fl oz.	ALMOND/BONE - CARTRIDGE	12	15.0	032628256361	73
25641	6 fl. oz.	BISCUIT/LINEN - TUBE DISPLAY	24	18.0	032628256415	28
25646	10 fl. oz.	BISCUIT/LINEN - CARTRIDGE	12	16.0	032628256460	28
<b>PLUMBERS CAULK - SILICONE™</b>						
<ul style="list-style-type: none"> <li>High-quality 100% pure professional grade sealant</li> <li>Excellent adhesion to most porous and non-porous materials</li> </ul>			<ul style="list-style-type: none"> <li>Tack-free in 30 minutes; completely cured in 24 hours</li> </ul>			
25671	3 oz.	WHITE - METAL TUBE DISPLAY	12	4.0	032628256712	107
25676	11 oz.	WHITE - CARTRIDGE	12	10.0	032628256767	107
25681	3 oz.	CLEAR - METAL TUBE DISPLAY	12	4.0	032628256811	107
25686	11 oz.	CLEAR - CARTRIDGE	12	11.0	032628256866	107
<b>PLUMBERS FIRESTOP SEALANT™</b>						
<ul style="list-style-type: none"> <li>Latex-based intumescent sealant</li> <li>Meets many applications and codes</li> </ul>			<ul style="list-style-type: none"> <li>Provides up to a 3-hour fire rating</li> </ul>			
25696	10 oz.	CARTRIDGE	12	11.0	032628256965	116
<b>HIGH TEMP RED</b>						
<ul style="list-style-type: none"> <li>For high temperature applications</li> <li>Flexible, durable, waterproof seal</li> </ul>			<ul style="list-style-type: none"> <li>Performs at temperatures ranging from -80° F to +600° F</li> </ul>			
25666	10.1 fl. oz.	RED - Cartridge	12	11.0	032628256668	117





Product No.	Size	Description	Ctn. Qty.	Ctn. Wt.	U.P.C. Code	MSDS
-------------	------	-------------	-----------	----------	-------------	------

### CUTTING OIL

- Contains activated sulfur-lard and extreme pressure - antiwear additives
- Contains no nitrosamine-forming compounds or chlorine additives
- Excellent lubrication for cutting sharp threads
- NSF registered/USDA authorized

40110	1 pt.	CLEAR	24	28.6	032628401105	43
40115	1 qt.	CLEAR	12	28.0	032628401150	43
40120	1 gal.	CLEAR	6	49.4	032628401204	43
40125	5 gal.	CLEAR	1	40.2	032628401259	43
40140	55 gal.	CLEAR	1	452.0	032628401402	43
40210	1 pt.	DARK	24	28.6	032628402102	44
40215	1 qt.	DARK	12	28.0	032628402157	44
40220	1 gal.	DARK	6	49.4	032628402201	44
40225	5 gal.	DARK	1	40.2	032628402256	44
40240	55 gal.	DARK	1	452.0	032628402409	44

### JET-STREAM PENETRATING OIL

- For speedy release of "frozen", rusted or corroded parts
- Safe for metals; will not harm painted surfaces

40300	12 oz.	AEROSOL CAN	12	12.5	032628403000	45
-------	--------	-------------	----	------	--------------	----

### LUBE OIL WITH EXTENDA-SPOUT

- Custom-formulated, multi-purpose lubricating oil
- Non-gumming, non-toxic, non-detergent, and will not foam during use
- Contains rust and corrosion preventatives
- Extendable spout

40404	4 oz.		24	6.9	032628404045	47
-------	-------	--	----	-----	--------------	----

### DUCK BUTTER®

- Water soluble pipe lubricant
- Adheres to wet and dry surfaces

40501	2 lb.		12	29.8	032628405011	74
40506	8 lb.		4	35.5	032628405066	74

### 300 DEGREE PLUMBERS GREASE

- Petroleum oil-based valve and faucet stem grease
- Waterproof; prevents corrosion
- Non-melting, non-hazardous

40601	2 oz.		24	4.2	032628406018	39
-------	-------	--	----	-----	--------------	----

### PRO-PORT™

- For easy access for behind-the wall fittings
- Easy installation - paintable

43008	8" x 8"	DISPLAY BOX	12	9.5	032628430082	999
43014	14" x 14"	DISPLAY BOX	12	24.3	032628430143	999

### BLACK MAGIC™ ASPHALT PAINT

- Weather and corrosion resistant asphalt-base coating

45210	1 gal.		4	33.2	032628452107	58
-------	--------	--	---	------	--------------	----