

| Product No. | Size | Description | U.P.C. Code | Carton Quantity | Ctn. Wt. |
|-------------|------|-------------|-------------|-----------------|----------|
|-------------|------|-------------|-------------|-----------------|----------|

PLUMBER'S PUTTY

- Stainless fixture setting compound for setting frames, faucets, strainer baskets, etc.
- Stays flexible and will not crack or shrink.
- Made of easily workable soft, pliable material.
- Not for use on marble, granite, plastic or any other dimensional stone.
- Meets Military Spec. TTP-1536A.

| | | | | | |
|--------|--------|---|---------------|-----|-----|
| 31166 | 14 oz. | Putty – Plastic container | 038753-311661 | 24 | 24 |
| 31166D | 14 oz. | Putty – Plastic container – Display | 038753-311661 | 30 | 30 |
| 311660 | 14 oz. | Putty – Plastic container – Mini Pallet | 038753-311661 | 270 | 270 |
| 31170 | 3 lb. | Putty – Plastic container | 038753-311708 | 6 | 20 |
| 31174 | 5 lb. | Putty – Plastic container | 038753-311746 | 6 | 32 |
| 31174D | 5 lb. | Putty – Plastic container – Display | 038753-311746 | 6 | 32 |



PIPE/GASKET LUBE

- Non-toxic, soft, paste like material for lubricating bell joint pipe gaskets.
- Will not deteriorate natural or synthetic rubber.
- Will not support bacteria.
- Dissolves in hot water.

| | | | | | |
|-------|----------|----------------|---------------|----|----|
| 30599 | 16 oz. | Pipe Lubricant | 038753-305998 | 24 | 30 |
| 30600 | 32 oz. | Pipe Lubricant | 038753-306001 | 12 | 25 |
| 30601 | Gallon | Pipe Lubricant | 038753-306018 | 4 | 34 |
| 30605 | 5 Gallon | Pipe Lubricant | 038753-306056 | 1 | 42 |



PIPE SEAL

- Caulking lead substitute for sealing cast iron soil pipe joints.
- Air dry putty compound packs easily and resists shrinkage.
- Forms a hard leakproof seal.
- For use whenever it is impractical to pour molten lead.

| | | | | | |
|-------|--------|-----------|---------------|----|----|
| 30614 | 16 oz. | Pipe Seal | 038753-306148 | 12 | 20 |
|-------|--------|-----------|---------------|----|----|



GRAY PIPE JOINT COMPOUND

- Non-hardening gray paste seals and lubricates threaded joints.
- For use on water, steam or air lines.
- Non-separating and non-toxic material.
- Not for use on plastic threads.

| | | | | | |
|--------|------------|------------------------------------|---------------|----|----|
| 31226 | 1 fl. oz. | Gray Pipe Joint Compound | 038753-312262 | 12 | 2 |
| 31226D | 1 fl. oz. | Gray Pipe Joint Compound – Display | 038753-312262 | 54 | 8 |
| 31227 | 4 fl. oz. | Gray Pipe Joint Compound | 038753-312279 | 12 | 7 |
| 31228 | 8 fl. oz. | Gray Pipe Joint Compound | 038753-312286 | 12 | 13 |
| 31228D | 8 fl. oz. | Gray Pipe Joint Compound – Display | 038753-312286 | 30 | 26 |
| 31235 | 16 fl. oz. | Gray Pipe Joint Compound | 038753-312354 | 24 | 46 |
| 31236 | 32 fl. oz. | Gray Pipe Joint Compound | 038753-312361 | 12 | 43 |



GREAT WHITE® PIPE JOINT COMPOUND WITH PTFE

- Lubricates and seals all threaded joints.
- White, non-hardening, non-separating, non-toxic paste.
- Withstands up to 3,000 PSI on gases from -50 to +400°F, and 10,000 PSI on liquids from -50 to +500°F.
- For use with water, steam, caustics or dilute acid lines.
- Can be used with plastic and metal threads.

| | | | | | |
|--------|------------|---|---------------|-----|----|
| 31229 | 1 fl. oz. | Great White® Pipe Joint Compound w/PTFE | 038753-312293 | 12 | 1 |
| 31229D | 1 fl. oz. | Great White® Pipe Joint Compound w/ PTFE – Display | 038753-312293 | 54 | 3 |
| 312291 | 1 fl. oz. | Great White® Pipe Joint Compound w/ PTFE – Gravity Feed | 038753-312293 | 120 | 6 |
| 31230 | 4 fl. oz. | Great White® Pipe Joint Compound w/ PTFE | 038753-312309 | 12 | 7 |
| 31230D | 4 fl. oz. | Great White® Pipe Joint Compound w/ PTFE | 038753-312309 | 48 | 7 |
| 31231 | 8 fl. oz. | Great White® Pipe Joint Compound w/ PTFE | 038753-312316 | 12 | 12 |
| 31231D | 8 fl. oz. | Great White® Pipe Joint Compound w/ PTFE | 038753-312316 | 30 | 12 |
| 31232 | 16 fl. oz. | Great White® Pipe Joint Compound w/ PTFE | 038753-312323 | 24 | 39 |
| 31233 | 32 fl. oz. | Great White® Pipe Joint Compound w/ PTFE | 038753-312330 | 12 | 40 |



GREAT BLUE® PIPE JOINT COMPOUND

- Flexible blue, non-hardening, non-separating, non-toxic paste, no odor, easy clean-up.
- Use on PVC, CPVC, ABS, polyethylene, polypropylene, iron, steel, copper or brass threads up to and including 2".
- Withstands up to 3,000 PSI on gases from -50° to +400° F and 10,000 PSI on liquids from -50° to +500° F
- ABS, cyclocac, polypropylene, iron, steel or copper.
- Lubricates and seals thread on water, natural gas, steam, air lines, caustics and dilute acids.

| | | | | | |
|--------|------------|---------------------------------|---------------|----|----|
| 31265 | 1 fl. oz. | Great Blue® Pipe Joint Compound | 038753-312651 | 12 | 2 |
| 31261 | 4 fl. oz. | Great Blue® Pipe Joint Compound | 038753-312613 | 12 | 7 |
| 31262 | 8 fl. oz. | Great Blue® Pipe Joint Compound | 038753-312620 | 12 | 12 |
| 31263 | 16 fl. oz. | Great Blue® Pipe Joint Compound | 038753-312637 | 24 | 39 |
| 312636 | 16 fl. oz. | Great Blue® Pipe Joint Compound | 038753-312637 | 6 | 10 |
| 31264 | 32 fl. oz. | Great Blue® Pipe Joint Compound | 038753-312644 | 12 | 40 |





| Product No. | Size | Description | U.P.C. Code | Carton Quantity | Ctn. Wt. |
|--|-------------|-----------------------------|---------------|-----------------|----------|
| WHITE GENERAL PURPOSE THREAD SEAL TAPE WITH PTFE | | | | | |
| <ul style="list-style-type: none"> Provides a clean, positive seal on threaded connections. A high density product that resists tearing and stretching for easy, efficient application. Available carded or packaged bulk on spools. Complies with Military Spec. No. A-A-58092 & UL31RO. 3 mils thick, 0.7 grams/cubic centimeter density. | | | | | |
| 31199 | 1/2" x 260" | PTFE White Thread Seal Tape | 038753-311999 | 144 | 6 |
| 31202 | 1/2" x 520" | PTFE White Thread Seal Tape | 038753-312026 | 144 | 7 |
| 31212 | 3/4" x 260" | PTFE White Thread Seal Tape | 038753-312125 | 144 | 6 |



| | | | | | |
|---|-------------|--|---------------|-----|---|
| YELLOW GAS LINE THREAD SEAL TAPE WITH PTFE | | | | | |
| <ul style="list-style-type: none"> Manufactured especially for natural gas, propane, butane, water, oil and chemical lines. Heavier than white tape with density of 1.35-1.50 grams/cubic centimeters, 4 mils thick. Complies with MIL-T-22230A (ASG), UL 31 RO, AGA 3226 and CAN/ULC-S642. Packaged on spools in convenient dispenser box. | | | | | |
| 31403 | 1/2" x 260" | PTFE Yellow Thread Seal Tape - Dispenser pack | 038753-314037 | 100 | 7 |
| 31403D | 1/2" x 260" | PTFE Yellow Thread Seal Tape - Display | 038753-314037 | 20 | 1 |



| | | | | | |
|---|-------------|--------------------------------------|---------------|----|---|
| PINK WATER LINE THREAD SEAL TAPE WITH PTFE | | | | | |
| <ul style="list-style-type: none"> Provides fast positive seal for water lines, sewage lines and sprinkler systems. Effective on metal or plastic threads. Complies with Mil. Spec. A-A 58092. Pink tape is 3 mils thick with density of 1.35-1.50 grams/cubic centimeter. Packaged on spools in a display carton. | | | | | |
| 31402D | 1/2" x 260" | PTFE Pink Thread Seal Tape - Display | 038753-314020 | 50 | 3 |



| | | | | | |
|--|--------|------------------------------------|---------------|----|----|
| CLEAR THREAD CUTTING OIL | | | | | |
| <ul style="list-style-type: none"> Protection helps make sharp clean threads while extending the life of your dies. Formulated for hand thread cutting machines. Anti-mist and non-staining formula is not affected by weather. | | | | | |
| 30200 | 16 oz. | Clear Cutting Oil (hand threading) | 038753-302003 | 12 | 13 |
| 30201 | 32 oz. | Clear Cutting Oil (hand threading) | 038753-302010 | 12 | 26 |
| 30202 | Gallon | Clear Cutting Oil (hand threading) | 038753-302027 | 6 | 50 |



| | | | | | |
|--|--------|------------------------------------|---------------|----|----|
| DARK THREAD CUTTING OIL | | | | | |
| <ul style="list-style-type: none"> Formulated for high speed cutting machines. A special mixture of sulfonated and chlorinated oils provides high film strength. Keeps machines running cooler and extends the life of your dies. Anti-mist and non-staining formula is not affected by weather. | | | | | |
| 30203 | 16 oz. | Dark Cutting Oil (speed threading) | 038753-302034 | 12 | 13 |
| 30204 | 32 oz. | Dark Cutting Oil (speed threading) | 038753-302041 | 12 | 26 |
| 30205 | Gallon | Dark Cutting Oil (speed threading) | 038753-302058 | 6 | 50 |



| | | | | | |
|--|--------|--|---------------|----|----|
| ALL PURPOSE LEAK DETECTOR | | | | | |
| <ul style="list-style-type: none"> Detects leaks quickly on all types of tubing, valves, cylinders, pressure tanks or other systems under air, gas or oxygen pressure. Functions in a -55°F to +160°F temperature range. Slow evaporation rate provides longer inspection time. | | | | | |
| 30209 | 8 oz. | All Purpose Leak Detector with dauber | 038753-302096 | 12 | 9 |
| 30211 | 16 oz. | All Purpose Leak Detector with trigger spray | 038753-302119 | 12 | 17 |
| 30212 | Gallon | All Purpose Leak Detector | 038753-302126 | 4 | 39 |



| | | | | | |
|---|--------|-------------------------------|---------------|----|----|
| PLUMBERS HAND CLEANER | | | | | |
| <ul style="list-style-type: none"> Safely removes plastic pipe cements from hands. Also removes varnish, enamels, grease and adhesives. Use with or without water. Freshly scented conditioning formula contains aloe, lanolin, jojoba and vitamin E. | | | | | |
| 30221 | 16 oz. | Hand Cleaner - squeeze bottle | 038753-302218 | 12 | 14 |

| Product No. | Size | Description | U.P.C. Code | Carton Quantity | Ctn. Wt. |
|--|-------|------------------------------------|---------------|-----------------|----------|
| FIX IT STICK EPOXY PUTTY | | | | | |
| <ul style="list-style-type: none"> Convenient multi-purpose sealing, patching and mending compound. Steel filled material, mixes in the hand and hardens in minutes. May be drilled, tapped, filed, sanded, sealed and painted when hardened. Non-toxic material contains no solvents and will not shrink. | | | | | |
| 31270 | 4 oz. | Fix It Stick Epoxy Putty – Display | 038753-312705 | 12 | 8 |



| | | | | | |
|--|--------|------------------------------|---------------|----|----|
| TUB-N-TILE CAULK | | | | | |
| <ul style="list-style-type: none"> White, flexible, latex sealant. Fills and seals cracks and joints. For caulking around showers, tubs, lavatories and sinks. Cleans up with soap and water. Can be used to reset loose tiles. Can be painted when dry with either oil base or latex paint. | | | | | |
| 30240 | 6 oz. | Tub-N-Tile Caulk – Tube | 038753-302409 | 24 | 8 |
| 30241 | 10 oz. | Tub-N-Tile Caulk – Cartridge | 038753-302416 | 24 | 30 |



| | | | | | |
|--|-------|--------------------------------|---------------|----|---|
| TUB-N-TILE ULTRA CLEAR SEALANT | | | | | |
| <ul style="list-style-type: none"> Applies white and dries clear. Flexible butyl acrylate formula adheres to porous surfaces such as wood and masonry. Cleans up with soap and water. Flexible material won't crack or peel and adheres tightly. Paintable with no offensive odors. | | | | | |
| 30235 | 6 oz. | Tub-N-Tile Clear Sealant- Tube | 038753-302355 | 12 | 6 |



| | | | | | |
|---|----------|-------------------------------------|---------------|----|----|
| SILICONE SEALANT | | | | | |
| <ul style="list-style-type: none"> Clear and white sealants for high performance sealing. Bonds to porcelain, ceramic, marble, fiberglass and most metals. Remains permanently elastic. When fully cured, recognized by USDA for use in meat and poultry plants. Meets Fed. Spec. TT-S-00230C Class A & TT-S-001543A Class A, Mil. Spec. 46106A, ASTM C920, FDA Regulation No. 21 CFR 177.2600. Withstands temperature from -60°F to 400°F. | | | | | |
| 30236 | 10.3 oz. | Silicone Sealant, Clear – Cartridge | 038753-302362 | 12 | 11 |
| 30237 | 10.3 oz. | Silicone Sealant, White – Cartridge | 038753-302379 | 12 | 11 |



| | | | | | |
|--|--|--------------------------|---------------|----|----|
| HEAVY DUTY WAX BOWL RING | | | | | |
| <ul style="list-style-type: none"> 100% pure petroleum wax gasket for setting any floor type closet bowl. Fits 3" or 4" waste lines and meets Military Spec. TTP-1536A. Provides a permanent seal impervious to vermin, odors, gases and acids. | | | | | |
| 31190 | | Heavy Duty Wax Bowl Ring | 038753-311906 | 48 | 25 |



| | | | | | |
|--|--|--|---------------|----|----|
| HEAVY DUTY WAX BOWL RING W/ SLEEVE | | | | | |
| <ul style="list-style-type: none"> 100% pure petroleum wax gasket for setting any floor type closet bowl. Fits 3" or 4" waste lines and meets Military Spec. TTP-1536A. Provides a permanent seal impervious to vermin, odors, gases and acids. Polyethylene sleeve extends discharge opening for a more positive seal assuring proper bowl alignment. | | | | | |
| 31194 | | Wax bowl ring with polyethylene sleeve | 038753-311944 | 24 | 15 |
| 31193 | | Flanged gasket w/ 1/2" x 2-1/4" brass bolts and nuts | 038753-311937 | 24 | 17 |





| Product No. | Size | Description | U.P.C. Code | Carton Quantity | Ctn. Wt. |
|--|------|--|---------------|-----------------|----------|
| REINFORCED WAX BOWL RING W/ SLEEVE | | | | | |
| <ul style="list-style-type: none"> • 100% pure petroleum wax gasket for setting any floor type closet bowl. • Provides a permanent seal impervious to vermin, odors, gases and acids. • Fits 3" to 4" waste lines and meets Military Spec. TT-P-1536A. • Polyethylene sleeve extends discharge opening for a more positive seal assuring proper bowl alignment. • Sponge provides resiliency. Expands and contracts with the bowl or building to prevent wax from settling. | | | | | |
| 31195 | | Urethane Reinforced Wax Bowl Ring with Polyethylene Sleeve | 038753-311951 | 24 | 14 |



| | | | | | |
|---|--|------------------------------|---------------|----|---|
| MAXWAX® WAX BOWL RING | | | | | |
| <ul style="list-style-type: none"> • 40% thicker than regular wax ring with a polyethylene sleeve to assure a tight seal. • 100% pure petroleum wax gasket for setting any floor type closet bowl. • Fits 3" to 4" waste lines and meets Military Spec. TT-P-1536A. • Polyethylene sleeve extends discharge opening for a more positive seal assuring proper bowl alignment. • Provides a permanent seal impervious to vermin, odors, gases and acids. | | | | | |
| 31188 | | MaxWax Bowl Ring with Sleeve | 038753-311883 | 12 | 7 |



| | | | | | |
|--|--|-----------------|---------------|----|---|
| URINAL WAX RING | | | | | |
| <ul style="list-style-type: none"> • Urinal wax ring has a urethane sponge to provide resiliency. | | | | | |
| 31187 | | Urinal Wax Ring | 038753-311876 | 24 | 3 |